

# DECORATIVE PANELS INTERNATIONAL MSDS - 014

## Smooth Panelboard

### 1. PRODUCT AND COMPANY INFORMATION

Product Code: Not applicable  
 Product Name: Smooth Panelboard  
 Brand Names:

Decorative Panels International, 2900 Hill Avenue, Toledo, Ohio 43607-2929  
**Telephone: (419) 535-5921**

### 2. COMPOSITION AND INGREDIENT INFORMATION

Component	CAS #	Exposure Limits	Cancer Designation
Wood Dust	NA	TLV-TWA = 1 mg/m <sup>3</sup>	MAK-1, NIOSH-Ca, TLV-A1, NTP-K
Linseed Oil	8001-26-1	TLV-TWA = 10 mg/m <sup>3</sup>	
Ferric Sulfate	10028-22-5	PNOS <sup>(2)</sup>	
Filler <sup>(1)</sup>			
Polyester Resin (cured)		PNOS <sup>(2)</sup>	
Crystalline Silica	14808-60-7	TLV-TWA = 0.05 mg/m <sup>3</sup> R	IARC-1, NIOSH-Ca, NTP-K, TLV-A2, MAK-1
Titanium Dioxide	13463-67-7	TLV-TWA = 10 mg/m <sup>3</sup>	NIOSH-Ca
PGME	107-98-2	TLV-TWA = 100 ppm	
Basecoat <sup>(1)</sup>			
Acrylic Resin (cured)		PNOS <sup>(2)</sup>	
Aluminum Silicate	1332-58-7	TLV-TWA = 2 mg/m <sup>3</sup> R	
Ethyl Alcohol	64-17-5	TLV-TWA = 1000 ppm	
Amorphous Silica	7631-86-9	PNOS <sup>(2)</sup>	
Topcoat <sup>(1)</sup>			
Acrylic Resin (cured)		PNOS <sup>(2)</sup>	
Formaldehyde	50-00-0	PEL-TWA = 0.75 ppm TLV-C = 0.3 ppm	EPA-B1, IARC-2A, NIOSH-Ca, NTP-R, OSHA-Ca, TLV-A2
Titanium Dioxide	13463-67-7	TLV-TWA = 10 mg/m <sup>3</sup>	NIOSH-Ca
PGMPE	1569-01-3	NE	
N-Butyl Alcohol	71-36-3	TLV-C = 20 ppm	
Ethyl Benzene	100-41-4	TLV-TWA = 100 ppm	IARC-2B, TLV-A3
Xylene	1330-20-7	TLV-TWA = 100 ppm	

(1) Cured filler, base, and topcoats do not contain significant residual amounts of volatile solvents.

(2) (PNOS): PEL-TWA = 15 mg/m<sup>3</sup>, total dust; PEL-TWA = 5 mg/m<sup>3</sup>, respirable fraction; TLV-TWA = 10 mg/m<sup>3</sup> inhalable particulate, 3 mg/m<sup>3</sup> respirable particulate.

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Contact with strong oxidizers or exposure to temperatures greater than 400<sup>0</sup> F may cause a fire. Smoke may contain carbon monoxide, aldehydes, and other toxic materials. Airborne wood and resin dust may explode when combined with an ignition source.

# DECORATIVE PANELS INTERNATIONAL

## MSDS - 014

### Smooth Panelboard

#### Potential Health Effects (based on expected use of product)

**EYE:** Dust may irritate the eyes.

**SKIN:** Dust may cause skin irritation.

**INGESTION:** Not known.

**INHALATION:** Dust can cause irritation to mucous membranes and the upper respiratory tract. Wood dust and formaldehyde are considered carcinogens.

#### 4. FIRST AID MEASURES

**EYES:** For dust exposure, immediately flush eyes with plenty of water for at least 15 minutes.

**SKIN:** Wash with soap and water. Get medical attention if irritation develops or persists.

**INGESTION:** Consult a physician.

**INHALATION:** Remove to fresh air, consult a physician.

**NOTE TO PHYSICIANS:** Exposure to dust may aggravate symptoms of persons with pre-existing respiratory tract conditions and may cause skin and gastrointestinal symptoms.

#### 5. FIRE FIGHTING MEASURES

##### FLAMMABLE PROPERTIES:

Flash point: Not applicable.

Combustible: Material may burn on contact with oxidizers or ignition sources.

##### FLAMMABLE LIMITS:

Lower flammable limit: Not applicable.

Upper flammable limit: Not applicable.

**AUTOIGNITION TEMPERATURE:** Typically 400-500° F.

**EXPLOSION HAZARD:** Airborne concentrations of combustible dust, when combined with an ignition source, can create an explosion hazard if the dust concentration exceeds 30 - 60 g/m<sup>3</sup>.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon dioxide, carbon monoxide, nitrogen oxides, aldehydes, cyanides, and other hazardous gases, vapors, and particles.

**EXTINGUISHING MEDIA:** Water, dry chemical and other agents rated for a wood fire (Type A fire). Use an extinguisher rated for a Type A fire.

**FIRE FIGHTING INSTRUCTIONS:** Evacuate the area and notify the fire department. If possible isolate the fire by moving other combustible materials. If the fire is small, use a hose-line or extinguisher rated for a Type A fire. If possible, dike and collect water used to fight fires. Fire fighters should wear normal protective equipment (full bunker gear) and positive-pressure self-contained breathing apparatus.

#### 6. ACCIDENTAL RELEASE MEASURES

Does not apply.

#### 7. HANDLING AND STORAGE

**HANDLING:** Provide ventilation or other measures so that dust levels are below the exposure limits listed in Section 2.

**STORAGE:** Keep dust away from ignition sources and store in a closed container. Consult NFPA 68 and 70 for additional information.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Control airborne dust concentrations below the exposure limits. Use only with adequate ventilation.

Effective Date: 5-21-04

Replaces: All Previous

# DECORATIVE PANELS INTERNATIONAL MSDS - 014

## Smooth Panelboard

**RESPIRATORY PROTECTION:** When respiratory protection is required, or dust concentrations are unknown, use a NIOSH/MSHA approved air-purifying respirator for dusts.

**SKIN PROTECTION:** Wear work gloves to prevent skin irritation.

**EYE PROTECTION:** Wear ANSI approved eye protection.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT:	NA	DENSITY:	28 - 70 lb/ft <sup>3</sup>
MELTING POINT:	NA	pH:	NA
VAPOR PRESSURE:	NA	ODOR:	Slight to none
VAPOR DENSITY:	NA	APPEARANCE:	4 ft by 8 ft hardboard prefinished on one side
SOLUBILITY IN WATER:	NA		

### 10. STABILITY AND REACTIVITY

**CHEMICAL STABILITY:** (CONDITIONS TO AVOID) Stable.

**INCOMPATIBILITY:** Keep away from high temperatures and strong oxidizers, such as concentrated nitric acid, oxygen, hydrogen peroxide, and chlorine.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, hydrogen cyanide, and other products of wood combustion.

**HAZARDOUS POLYMERIZATION:** Will not occur.

### 11. TOXICOLOGICAL INFORMATION FOR WOOD DUST AND FORMALDEHYDE

#### WOOD DUST

Wood dust is known to be a human carcinogen. An increased incidence of adenocarcinoma of the nasal cavities and paranasal sinuses was observed in studies of people whose occupations are associated with wood dust exposure. (10<sup>th</sup> Edition of the National Toxicology Program's Report on Carcinogens) Wood dust from some tree species may induce sensitization.

#### FORMALDEHYDE

**Chronic (Cancer) Information:** See Section 2 for carcinogenicity categories.

**Teratology (Birth Defect) Information:** No hazards reported.

**Reproduction Information:** Reproductive effects in animals have been reported in RTECS for formaldehyde.

**Sensitizer:** Exposure to low doses of formaldehyde may cause an allergic reaction.

### 12. ECOLOGICAL INFORMATION

These wood products are not expected to pose an ecological hazard as a result of their intended uses.

### 13. DISPOSAL CONSIDERATIONS

Dispose of waste according to local, state/provincial, and federal requirements.

### 14. TRANSPORTATION INFORMATION - Hazardous Materials Table 172.101

Shipping Name	NA	Packing Group	NA
Hazard Class	NA	Placards/Labels	NA
Identification No.	NA	Special Provisions	NA

### 15. REGULATORY INFORMATION

OSHA: Hazard Communication	CFR 1910.1200 (b)(6)(iv)	CERCLA RQ:	NA
EPCRA EHS RQ Section 302:	NA	EPA CAA Section 112(r)	NA

**DECORATIVE PANELS INTERNATIONAL  
MSDS - 014**

**Smooth Panelboard**

EPCRA Section 313:	NA	Uniform Fire Code	NA
--------------------	----	-------------------	----

# DECORATIVE PANELS INTERNATIONAL

## MSDS - 014

### Smooth Panelboard

#### 16. OTHER INFORMATION

This MSDS is intended solely for safety education and not for use as specifications or warranties. The information in this MSDS was obtained from usually reliable sources and is provided without any representation for warranties regarding the accuracy or correctness. Since the handling, use, and storage is beyond our control, DPI assumes no responsibility and disclaims liability for any loss, damage, or expense arising therefrom.

#### ABBREVIATIONS:

ANSI	American National Standards Institute
ASTM	American Society for Testing and Materials
C	Ceiling
CAA	Clean Air Act
CAS	Chemical Abstract Services (identifies specific chemical)
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CFR	Code of Federal Regulations
Dust	A finely divided solid 0.017 in. or less in diameter that is capable of passing through a U.S. No. 40 standard sieve
EHS	Extremely Hazardous Substance
EPA-B1	Environmental Protection Agency-Limited evidence of carcinogenicity from epidemiological studies
EPCRA	Emergency Planning and Community Right-To-Know Act
IARC-2A	International Agency for Research on Cancer-Probably Carcinogenic to Humans
IARC-2B	International Agency for Research on Cancer-Possibly Carcinogenic to Humans
g/m <sup>3</sup>	Grams per cubic meter
mg/m <sup>3</sup>	Milligrams per cubic meter
lb/ft <sup>3</sup>	Pounds per cubic foot
MAK-1	Substances that cause cancer in man
MAK-3	Substances which cause concern that they could be carcinogenic for man
MAK-3B	Substances for which <i>in vitro</i> tests or animal studies have yielded evidence of carcinogenic effects
MSHA	Mine Safety Health Act
NFPA	National Fire Protection Association
NIOSH-Ca	National Institute of Occupational Safety and Health-Potential occupational carcinogen, with no further categorization
NTP-K	National Toxicology Program-Known to be a carcinogen
NTP-R	National Toxicology Program-Reasonably anticipated to be a carcinogen
OSHA-Ca	Occupational Safety and Health Administration-Carcinogen defined with no further categorization
PNOS	Particle not otherwise specified
PEL	OSHA Permissible Exposure Limit
ppm	Parts per million
R	Respirable
RTECS	Registry of Toxic Effects of Chemical Substances
RQ	Reportable Quantity
TLV-A1	Threshold Limit Value-Confirmed Human Carcinogen
TLV-A2	Threshold Limit Value-Suspected Human Carcinogen
TLV-A3	Threshold Limit Value-Confirmed Animal Carcinogen with Unknown Relevance to Humans
TWA	8-hour time-weighted average exposure

#### BIBLIOGRAPHY:

1. Guide to Occupational Exposure Values, American Conference of Governmental Industrial Hygienists, 2002.
2. Registry of Toxic Effects of Chemical Substances, National Institute for Occupational Safety and Health, Q-1, 2003.
3. Dangerous Properties of Industrial Materials, Sax's, 1998 CD-Folio.
4. CESARS, Chempendium, Canadian Centre for Occupational Health and Safety, Q-1, 2003.
5. Integrated Risk Information System, EPA, on-line.
6. EPA Title III List of Lists.
7. Handbook of Fire Protection Engineering, 2<sup>nd</sup> Edition.
8. 49 CFR 172.101, Hazardous Materials Table, from Chempendium. Q1, 2003.
9. Documentation of the TLVs®, American Conference of Governmental Industrial Hygienists, 2002.
10. 10<sup>th</sup> Edition of the National Toxicology Program's Report on Carcinogens, 2002.
11. TLVs® and BEIs®, American Conference of Governmental Industrial Hygienists, 2003.

Note: Decorative Panels International periodically updates and revises its product information. To verify this information, please call the number listed in Section 1.

**DECORATIVE PANELS INTERNATIONAL  
MSDS - 014**

Smooth Panelboard